



Pioneer All-in-One (SL15)

The Pioneer All-in-One terminal is a compact system consisting of a rugged 15" touchscreen and fully integrated Epson thermal receipt printer. The terminal is simple to set up and reduces cable clutter.



Specifications

Item	Description
Display Size	15" 1024 x 768
Dimensions (HxWxD)	16.3 x 15 x 13
Weight	26 lbs
Spill Proof	IP65 rated front panel only
Operating System	Linux
Network/Ethernet	Wired network via Ethernet
Connectivities	5X USB 2.0/Core: 2X USB 2.0, 3X USB 3.0
Mounting Options	Desktop Sline Base (Epson printer built-in) or no printer for desktop or wall mounting
Operating Environment	0°C to 40°C, 20% to 80% Humidity
Warranty	3 Years
Optional External Peripherals	RFID or barcode readers



Alfred AD-215 Self-service kiosk

The Alfred self-service kiosk features a 21.5" touchscreen, built-in thermal printer, and 2D barcode scanner. With flexible mounting options and modern design, this kiosk will fit in any setting.



Specifications

Item	Description
Display Size	21.5", 16:9, 1920 x 1080 (300 nits)
Dimensions	Floor Stand Landscape: 524 x 1482 x 401 mm / 20.6 x 15.8 in (AD-215) Portrait: 380 x 1572 x 401 mm / 15 x 61.9 x 15.8 in (AD-215) Desktop Stand Landscape: 524 x 728 x 324 mm / 20.6 x 28.7 x 12.8 in (AD-215) Portrait: 324 x 818 x 324 mm / 12.8 x 32.2 x 12.8 in (AD-215)
Reliability	System operating temperature: 0 ~ 40°C / 32 ~ 104°F System humidity: 15% ~ 80% Storage temperature: -20 ~ 60°C / -4 ~ 140°F
Wi-Fi	Wi-Fi option available
Printer	3" thermal printer
Mounting Options	Desktop stand, floor stand or wall mount (Standard VESA)
I-O Ports	1 x Intel LAN (IEEE 802.3 10/100/1000 (Mbps)) 4 x USB 3.2 + 2 x USB 2.0 3 x USB 3.2 + 3 x USB 2.0
Barcode Scanner	2D barcode scanner
Peripherals Options	MSR, EMV terminal brackets for supported credit card terminals



Cleo C14 Terminal

The Cleo C14 is an all-in-one POS terminal with a 14.1" touchscreen and built-in thermal printer. The compact design makes this an ideal solution for areas with limited counter space.

The spill-proof display and solid-drive make this unit resistant to dust, shocks, and vibrations.



Specifications

Item	Description
Screen Size/Resolution	C10-1E & C14-1E (Elkhart Lake): C14: 14.1" (1366 x 768, 220 nits)
Dimensions (WxHxD)	C14: 13.41" x 12.41" x 9.73" / 341 mm x 315 mm x 247.13 mm
Weight	C14: 8.82 lbs / 4 kg
Aspect Ratio	16:9
Touch	PCAP touch
External I/O Interface	4 x USB 3.2 + 2 x USB 2.0 1 x LAN (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45) 1 x DC +24V input
Printer	3" thermal printer
Power Adapter	Input: 100 ~ 240V / Output 24V, 72W
Reliability	System operating temperature: 0 ~ 104°F / 0 ~ 40°C System humidity: 15% ~ 80% Storage temperature: -4 ~ 140°F / -20 ~ 60°C



M3W-2 Rugged Tablet

The M3W-2 enterprise tablet offers a powerful mobile POS technology designed especially for retail and hospitality environments.

Built Tough for Busy Environments

This tablet is ready for the most demanding environments. It has an IP54 sealing rating, which means it is highly resistant to dust and moisture, including spills that sometime occur in busy retail stores or restaurant.

POS Base Adds Utility

While the M3W-2 works well as a mobile, handheld device, its POS base options give it the flexibility to be a countertop POS terminal. Base options have multiple I/O ports for connection to a printer, cash drawer, and ethernet. A key lock secures the tablet in place.

Special Features

- Wireless communication capabilities
- Easy all-day use for indoor and outdoor

Optional

- POS base
- Battery charging cradle
- Built-in barcode scanner
- MSR scanner



M3W-2 Spec Sheet

Specifications

Item	Description
Display Size	10.1" 16:10 1280 x 800 350 nits
Dimensions (WxHxD)	278 x 199 x 24.2 mm / 10.95 x 7.83 x 0.95 in
Weight	2.43 lbs / 1.1 kgs
Spill & Dust Resistant	IP54 Certified
Operating System	Linux
Network	Wired network via Ethernet with dock wireless capable
Drop	3 ft (meter)
Printer	3" thermal printer
I/O Interface	1 x Type ~ A USB 3.0 1 x Micro B USB 2.0 1 x DC Jack 1 x POGO Pins
Battery	Main Battery: 7.4V, 4600 mAh Swappable battery: 3.8V / 250 mAh
Peripheral Options	RFID 2D barcode scanner POS Base, battery charging cradle
Reliability	System operating temperature: 0 ~ 40°C / 32 ~ 104°F System humidity: 15% ~ 80% Storage temperature: -20 ~ 60°C / -4 ~ 140°F



POS Base M3W-2 Specifications



PAR//NER

Item	X3-10
Mechanism	POS Base Mini
USB	4
COM	4
Ethernet	1
Cash Drawer	1
DC	12V 7.5A 90W
Dimensions (WxHxD)	278 x 225.25 x 321.1